


VIDEO CONFERENCE AT YOUR DESK

Wizyconf offers you **the best videoconferencing experience ever**. Wildix Wizyconf videoconference solution is **fully integrated into the company communication system** and **does not require installation** of any additional software or hardware components.

Everything you need is the web browser. Easily start a videoconference with internal and external users right from your Collaboration web interface.

Wildix offers additional equipment to ensure the best user experience in large conference room — **Wizyconf-Huddle** for small conference rooms.

WIZYCONF HIGHLIGHTS



- Based on WebRTC
- No installation, plugin free
- Instant access via a link, also for external users
- Chat and private messaging, HD video & audio
- Access in audio-only mode possible
- Speaker auto-detection
- Tiles and Sidebar views
- Conference scheduling
- Desktop sharing
- Mute all/ Mute everyone except
- Conference recording (audio, video, screen sharing)
- Live streaming to Facebook, YouTube
- Raise a hand


WIZYCONF-HUDDLE

A **huddle room** is a collaboration space of the future -- a small room, equipped with teleconferencing system, where 3-5 people can gather for short meetings to discuss projects, strategize and take decisions.

Wizyconf-Huddle is a Plug&Play solution for your Huddle Rooms.

WIZYCONF-HUDDLE HIGHLIGHTS

- 120° wide angle webcam, Full HD
- No need of remote control
- 360° microphone
- All-in-one USB-C cable (USB-A adapter included)
- Portable case for easy transportation



WIZYCONF-HUDDLE TECH SPECIFICATONS

- Mechanically adjustable (up and down) lens: 1/2.8, fixed focus, 120° angle
- Image sense: Full HD CMOS sensor
- Video: 1080P (1920*1080 pixel)
- OS: Windows / MacOS
- Touch keypad: Mic on / off; Volume + / -
- Omnidirectional microphone with 256ms acoustic echo cancellation and dynamic noise reduction
- Network interface: USB-C(USB-A adapter included)
- Power: USB cable supply (5V /500mA)
- Temperature: 5° - 55° C / 41° - 131° F
- Storage: -10° - 55° C / 14° - 131° F
- Humidity: 20-85% non-condensed
- Noise level: <48db
- Full duplex audio
- Loudspeaker: 10 adjustable ranges up to 94dBA; frequency response: 300 to 3400Hz
- Weight: 465g
- Size: 235*62*62mm