

Wildix FXS media gateways serve to connect analog phones and fax machines to the Wildix PBX.

HIGHLIGHTS

- PoE Support (2-4FXS)
- Flash hook support
- TLS/ SRTP support
- MWI support (24FXS)
- CE, FCC compliance (4-24FXS)
- Differentiated ringtones for internal / external call class



TECH SPECIFICATIONS

W02FXS	W04FXS	W24FXS
Physical interfaces		
<ul style="list-style-type: none"> • 2 x RJ-45 10/100Mbps • 2 x RJ11 connectors 	<ul style="list-style-type: none"> • 2 x RJ-45 10/100Mbps • 4 x RJ11 connectors 	<ul style="list-style-type: none"> • 1 x RJ-45 10/100Mbps • 24 RJ11 + 1 RJ21 connectors
FXS		
<ul style="list-style-type: none"> • Dial Mode: DTMF and Pulse • Pulse: 10 and 20 PPS • Caller ID: DTMF/FSK CLI Presentation • Max cable length = 1 km • Reversed polarity • Programmable Call Progress Tone 	<ul style="list-style-type: none"> • Dial Mode: DTMF and Pulse • Pulse: 10 and 20 PPS • Caller ID: DTMF/FSK CLI Presentation • Max cable length = 0.8 km • Reversed polarity • Programmable Call Progress Tone 	<ul style="list-style-type: none"> • Dial Mode: DTMF and Pulse • Pulse: 10 and 20 PPS • Caller ID: DTMF/FSK CLI Presentation • Max cable length = 3 km • Reversed polarity • Programmable Call Progress Tone • Message Waiting Indicator (MWI)
Power supply		
<ul style="list-style-type: none"> • 100-240VAC, 50-60 Hz; 12 VDC, 1.5 A (optional, WMP code: PS-12V2A) • PoE 802.3af, class 0 • Power output: 48 V 	<ul style="list-style-type: none"> • 100-240VAC, 50-60 Hz; 12 VDC, 1 A (optional, WMP code: PS-12V2A) • PoE 802.3af, class 0 	<ul style="list-style-type: none"> • 100-240V, 50-60Hz (WMP code: PowerCord-UK/ USA/ EU)
Max Power Consumption		
<ul style="list-style-type: none"> • 5.3 W 	<ul style="list-style-type: none"> • 5 W 	<ul style="list-style-type: none"> • 36 W
Environmental		
<ul style="list-style-type: none"> • Operating Temperature: 0 °C ~ 45 °C • Storage Temperature: -20 °C ~80 °C • Humidity: 10%-90% Non-Condensing 	<ul style="list-style-type: none"> • Operating Temperature: 0 °C ~ 45 °C • Storage Temperature: -20 °C ~80 °C • Humidity: 10%-90% Non-Condensing 	<ul style="list-style-type: none"> • Operating Temperature: 0 °C ~ 45 °C • Storage Temperature: -20 °C ~80 °C • Humidity: 10%-90% Non-Condensing
Physical dimensions		
<ul style="list-style-type: none"> • 195*133*34mm 638 g 	<ul style="list-style-type: none"> • 195 x 135 x 35mm 600 g 	<ul style="list-style-type: none"> • 440 x 44 x 250 mm 3000 g