

Vision is an Android device, WebRTC ready, it is equipped with 7" display and a 2 megapixel webcam. You can receive video calls from another Vision, from a PC, from a doorphone or from another Android or iOS device. Vision is the phone for your WebRTC video conferences.



VISION HIGHLIGHTS

- Android 9 OS
- 7" color display TFT LCD 1024*600 with capacitive touchscreen
- Presence & Chat; 120 BLF keys
- 2 x Gigabit port 10/100/1000
- PoE IEEE 802.3af
- 2 MP webcam
- 802.3az Green Ethernet
- Audio HD wideband
- WiFi 802.11b/g/n; USB Type-C; Bluetooth
- WebRTC video conferencing
- Access to PBX phonebooks
- Call history sync
- Headset USB/ Bluetooth Audio Support

VISION TECH SPECIFICATIONS

Phone & PBX

- Android 9 OS
- Presence & Chat
- Support of WebRTC-based Wizyconf video conference
- New Voicemail / Missed call / New call notification
- Online access to PBX phonebooks
- Sync of call history and missed call notifications
- Selection and upload of ringtones
- Intercom, paging, speed dial, call on hold, 5-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold
- Multi-language support

Audio

- HD audio with wideband codec Opus
- Narrowband codec G.711a, ulaw, G.729
- Full-duplex speaker
- Echo canceller

Security & Networking

- SIP TLS; QoS VLAN; RTP/RTCP; SRTP

Compliances

- HAC compliant
- CE/ FCC/ UKCA Standards compliant

Supported Headsets

- WHS-MONO / WHS-DUO over 3.5 mm cable
- WHS-BT (mute / volume / call control support)
- Mono/ DuoLED, Mono/ DuoLED-BT
- 3rd party headsets: <https://wildix.atlassian.net/wiki/x/DhTOAQ>

Physical

- Up to 120 BLF keys
- 7" color display, capacitive touchscreen, Resolution 1024*600, 16:9 Wide Screen Aspect Ratio
- 1 x RJ9 handset port; 1x 3.5mm headset jack; 1 x HDMI video out port
- Flash Memory 8GB, 2GB DDR3 Memory
- Bluetooth 4.0; 1 x USB Type-C; WiFi 802.11 b/n/g
- LED buttons (Mute, Audio output, Voicemail)
- 2MP CMOS webcam with privacy shutter
- 802.3az Green Ethernet
- Foot stand
- Optional Power Adapter: (Code: PS-12V2A) Input AC 100-240 V; Output DC 12 V/ 1 A
- Power consumption ~12 W
- PoE class 0, IEEE 802.3af
- Dimensions: 250x210x98 mm, weight: 1.72kg
- Operating t°: 32~104 °F, 0~40 °C; Storage t°: -4~158 °F, -20~70 °C; Humidity: 10 to 90% Non-condensing

