

**SuperVision** is the exclusive desk phone for Top Managers.

**FEATURES - SUPERVISION**

- Android OS
- 8" color display 1280\*800
- Presence & Chat; 120 BLF keys
- 2 x Gigabit port 10/100/1000
- 5 MP webcam
- Magnetic hook
- Audio HD wideband
- Dual band WiFi 2.4Ghz / 5Ghz
- WebRTC video conferencing; Wallboard
- Headset USB Audio Support
- LED buttons (Voicemail, Mute, Audio output)



SuperVision

**TECH SPECIFICATIONS - SUPERVISION**

**PHONE & PBX**

- Android OS v. 5.1
- Presence & Chat
- Up to 120 BLF keys
- Support of WebRTC-based ubiconf video conference
- New Voicemail / Missed call / New call notification
- Online access to PBX phonebooks
- Sync of call history and missed call notifications
- Selection and upload of ringtones
- Intercom, paging, speed dial, call on hold, 5-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold
- Multi-language support

**AUDIO**

- HD audio with wideband codec G.722
- Narrowband codec G.711a, ulaw, G.729
- Full-duplex speaker
- Echo canceller

**SECURITY & NETWORKING**

- SIP TLS; QoS VLAN; RTP/RTCP

**SUPPORTED HEADSETS**

- WHS-MONO / WHS-DUO over USB connector (mute / volume / call control support) or 3.5 mm
- WHS-BT (mute / volume / call control support)
- Mono/ DuoLED (full status LEDs support coming later)
- 3rd party headsets: <https://confluence.wildix.com/x/DASIAQ>

**PHYSICAL**

- 8" color display, 1280x800
- Capacitive touchscreen
- 1 x RJ9 handset port
- 1 x 3.5mm headset jack
- 1 x HDMI video out port
- Memory: RAM 2GB, ROM 16GB
- Bluetooth 4.1
- 1 x USB 2.0
- Support of USB Headset Audio
- WiFi 802.11 b/n/g Dual band 2.4Ghz / 5Ghz
- 5MP CMOS removable webcam
- 802.3az Green Ethernet
- PoE class 0, IEEE 802.3af
- Phone size: 260 x 230 x 90mm
- Phone weight (with handset): 1.8kg

**POWER PERFORMANCE**

- Max power consumption: 12W

**ENVIRONMENTAL**

- Operating Temperature: 0 ~ 40°C / 32° ~ 104°F
- Storage Temperature: -20 ~ 70°C / -4°~ 158°F
- Storage Humidity: 10% to 90% Noncondensing

VoIP phones datasheets:

