

WP410 is a basic VoIP desk phone, perfect as an unattended phone for calling.

### WP410 HIGHLIGHTS

- Display: 132\*64 LCD
- 2 x Port 10/100
- PBX phonebooks
- 4 BLF keys (2 pages)
- PoE IEEE 802.3af
- Call history sync
- Quick DND key
- VM notification
- Visual / audio BLF
- Presence monitoring



### TECH SPECIFICATIONS

#### Phone & PBX

- Presence
- New Voicemail / Missed call / New call notification
- Online access to PBX phonebooks
- Sync of call history and missed call notifications
- PBX ringtones
- Intercom, paging, speed dial, hold, 3-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold
- Multi-language support

#### Audio

- Narrowband codec G.711a, ulaw, G.729
- Full-duplex speaker
- Echo canceller

#### Security & Networking

- SIP TLS; QoS VLAN; RTP/RTCP

#### Physical

- WP410: 4 BLF (software keys)
- WP410: 2.3" display with backlight 132\*64
- 1 x RJ9 headset port; 1 x RJ9 handset port
- Optional Power Adapter: Input AC 100-240 V; Output DC 5 V / 1 A
- Max power consumption: WP410: 1.3W
- PoE IEEE 802.3af WP410: PoE class 1
- WP410: 2 x RJ45 10/100 Mb Ethernet ports
- Giftbox size & weight: WP410 207\*197\*102 mm, 0.8 kg;
- Operating t°: 32~104 °F, 0~40 °C; Storage t°: 14~122 °F, -10 ~ 50 °C; Humidity: 10 to 90 % Non-condensing