

WP410 is a basic VoIP desk phone, perfect as an unattended phone for calling.

**WP410 HIGHLIGHTS**

- Display: 132\*64 LCD
- 2 x Port 10/100
- PBX phonebooks
- 4 BLF keys (2 pages)
- PoE IEEE 802.3af
- Call history sync
- Quick DND key
- VM notification
- Visual / audio BLF
- Presence monitoring



**TECH SPECIFICATIONS**

**Phone & PBX**

- Presence
- New Voicemail / Missed call / New call notification
- Online access to PBX phonebooks
- Sync of call history and missed call notifications
- PBX ringtones
- Intercom, paging, speed dial, hold, 3-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold
- Multi-language support

**Audio**

- Narrowband codec G.711a, ulaw, G.729
- Full-duplex speaker
- Echo canceller

**Security & Networking**

- SIP TLS; QoS VLAN; RTP/RTCP

**Physical**

- 4 BLF (software keys)
- 2.3" display with backlight 132\*64
- 1 x RJ9 headset port; 1 x RJ9 handset port
- Optional Power Adapter (code: PS-5V2A): Input AC 100-240 V; Output DC 5 V / 2 A
- Max power consumption: 1.3W
- PoE IEEE 802.3af WP410: PoE class 1
- 2 x RJ45 10/100 Mb Ethernet ports
- Giftbox size & weight: 207\*197\*102 mm, 0.8 kg
- Operating t°: 32~104 °F, 0~40 °C; Storage t°: 14~122 °F, -10 ~ 50 °C; Humidity: 10 to 90 % Non-condensing

VoIP phones datasheets:

