

WorkForce is the Office Phone for your employees. It is perfect for amplifying your efficiency and monitoring your coworkers' availability thanks to the integrated Collaboration feature. The only desk phone that comes with two spiral handset cords: 2.5 m (8 feet) and 3.5 m (11.5 feet).

HIGHLIGHTS

- USB-Type C input
- USB Headset-compatible
- USB Bluetooth dongle connectivity
- New, faster chipset
- Opus compatibility
- 5G / WiFi dongle-ready
- Hearing Aid Compatible
- Presence monitoring
- 2.8" color display 320*240
- Caller image
- 2 x Gigabit Port 10/100/1000
- PoE IEEE 802.3af
- Audio HD wideband
- Max 16 BLF keys (2 pages)
- Visual/ audio BLF
- 802.3az Green Ethernet



TECH SPECIFICATIONS

Phone & PBX

- Presence
- New Voicemail / Missed call / New call notification
- Online access to PBX phonebooks
- Sync of call history and missed call notifications
- PBX ringtones
- Intercom, paging, speed dial, hold, 3-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold
- Multi-language support

Audio

- HD audio with wideband codec G.722 Narrowband codec G.711a, ulaw, G.729, Opus
- Full-duplex speaker
- Echo canceller

Security & Networking

- SIP TLS; QoS VLAN; RTP/RTCP
- SRTP

Supported Headsets

- RJ-9 connector, USB connector
- WHS-MONO, WHS-DUO, WHS-BT (mute / volume / call control support, USB dongle is required)
- MonoLED, DuoLED (full status LEDs support starts from firmware v. 65.145.2.7)
- 3rd party headsets: <https://confluence.wildix.com/x/DASIAQ>

Physical

- 16 BLF (8 physical + 8 software keys)
- 2.8" color display with backlight 320*240
- 1 x RJ9 headset port; 1 x RJ9 handset port; 2 x USB Type-C inputs for a USB headset and WorkForce WiFi Dongle (available as a HWaaS item)
- 2 x spiral handset cords, 2.5 m (8 feet) and 3,5 m (11.5 feet)
- 802.3az Green Ethernet
- PoE IEEE 802.3af Class 2
- Optional Power Adapter (WMP code: PS-5V2A): Input AC 100-240 V; Output DC 5 V/ 2 A Max power consumption: 2.857W
- 2 x RJ45 10/100/1000 Mb Ethernet ports
- Giftbox size & weight: 274*258.5*142 mm, 1.6 kg
- Operating t°: 32~104 °F, 0~40 °C; Storage t°: 14~122 °F, -10 ~ 50 °C; Humidity: 10 to 90 % Non-condensing

VoIP phones datasheets:

